

COLAS PRODUCTS DATA SHEET

COLSEAL



Colseal is a pre-mixed slurry seal for sealing utility reinstatement and patch repairs. It is also ideal for sealing pre-surface dressing patches. It can also be used for covering score marks and for the treatment of driveways and pathways.

WHERE TO USE?

- Carriageways
- Footways
- Driveways

PREPARATION

The surface should be clean, dry and free of any loose chippings/debris (the treatment and removal of any weeds and moss should be carried out prior to laying preparation). Use masking tape to protect any kerbs/ironwork etc. from being covered (this is to be removed while the **Colseal** is still wet).

APPLICATION

Mix thoroughly before use using a drill paddle.

Pour onto surface in manageable amounts and using a soft brush with handle or squeegee, spread evenly over the surface to the recommended thickness of approximately 1.5-2mm, promptly finishing this area in the same directional brush stroke.

If a thickness greater than 1.5-2mm is required we recommend an additional application but it must be ensured that the first application is set fully before reapplying.

The material should be applied on a dry day at temperatures of 10°C and rising with no possibility of rainfall. Setting times vary with temperature. At the recommended thickness setting times will be, at 25°C approximately 1-3 hours and at 10°C 3-6 hours.

COVERAGE

1 x 25kg bag will cover approximately 10-14m² @ 1.5 - 2mm thickness, depending on surface texture.

PACKAGING

Colseal is supplied in 25kg buckets (36 x 25kg per pallet) or cardboard boxes containing 40 x 25kg bags.

STORAGE

Store in a cool, dry place, protect from frost.

STANDARDS

Supplied in accordance to ISO9001.

SAFETY

For full safety information, please request the **Colseal** Safety Data Sheet 152 using the contact information below.

NATIONAL SALES OFFICE

Loushers Lane
Warrington
Cheshire
WA4 6RZ
T: 01925 632 616
E: product.sales@colas.co.uk



WE OPEN THE WAY