

# COLAS PRODUCTS DATA SHEET

## GRIPSTRIPS



**Gripstrip** is an anti-skid, self-adhesive, overbanding joint and crack sealing tape. **Gripstrip** consists of an extruded bituminous compound modified with elastomers and fast bonding resins.

### WHERE TO USE?

- Horizontal cracks in asphaltic roads
- Transverse and longitudinal joints
- Trench reinstatements
- Patch repairs
- Drain or manhole frames

### PREPARATION

Ensure that the joint or crack is dry, clean and free from dust, fuel and oil spillage. For best results use when ambient temperature is 15°C or above. **Gripstrip** should not be applied to cracks wider than 10mm unless the crack has been pre-filled with approved material such as **Jointfill A2**, **Jointfill N1 & N2** or **Leoseal R**.

### APPLICATION

**Gripstrip** is applied to the road surface manually or with a specially adapted trolley. It is self-adhesive with the underside protected by peel off backing paper.

Once laid heavy foot pressure should be applied to assist adhesion. Applied **Gripstrip** will become embedded through trafficking.

### COVERAGE

Each roll will overband 25 linear metres.

### PACKAGING

**Gripstrip** is supplied in a box with 2 x 40mm x 25m rolls.

### STORAGE

Keep in dry store under cover.

### STANDARDS

**Gripstrip** has a skid resistance value of  $\geq 60$  and therefore complies with the requirements of the New Roads and Street Works Act.

### SAFETY

For full safety information, please request the **Gripstrip** Safety Data Sheet 94 using the contact information below.

#### NATIONAL SALES OFFICE

Loushers Lane  
Warrington  
Cheshire  
WA4 6RZ  
T: 01925 632 616  
E: [product.sales@colas.co.uk](mailto:product.sales@colas.co.uk)



WE OPEN THE WAY