

COLAS PRODUCTS DATA SHEET

COLSPRAY



Colspray is a rapid setting, cold applied bitumen spray designed for sealing vertical joints. **Colspray** can also be used as a tack coat helping to prevent the ingress of water.

WHERE TO USE?

- Transverse or longitudinal vertical joints
- Trench reinstatements
- Patch repairs
- Drain or manhole frames
- Kerb channels

PREPARATION

RS Bitukold should not be applied in ambient temperatures of less than 5°C. Ensure surface is clean and free from loose material, oil, grease, standing water and weeds.

APPLICATION

Ensure that the surface is clean and free from loose materials, oil, grease, standing water and weeds.

APPLICATION

Shake can vigorously before use. Turn can upside down and apply **Colspray** in even strokes with nozzle 200-300mm away from the surface to be treated. Ensure complete coverage. After use spray briefly with can in upright position to clear nozzle.

COVERAGE

The coverage rate for **Colspray** should be 0.7 to 1.5 kg/m², depending on the texture and porosity of the surface.

PACKAGING

Colspray is supplied in 750ml aerosol cans (12 per pack).

STORAGE

- Caution: pressurised container, protect from sunlight
- Do not pierce or burn even after use
- Do not expose to temperatures exceeding 50°C
- Do not spray on a naked flame or any incandescent material
- Keep out of reach of children

STANDARDS

Colspray complies with BS 594987 Clause 6.8 joints, vertical face coating.

SAFETY

For full safety information, please request the **Colspray** Safety Data Sheet 149 using the contact information below.

NATIONAL SALES OFFICE

Loushers Lane
Warrington
Cheshire
WA4 6RZ
T: 01925 632 616
E: product.sales@colas.co.uk



WE OPEN THE WAY