


CE marking information – Colas Ltd

 0836	
Colas Ltd, Wallage Lane, Rowfant West Sussex RH10 4NF 13 C2 0836-CPR-13/F035	
EN 13808 <i>Cationic bituminous emulsion</i> Surfix 80S C69BPF2/3 <i>intended to be used for surface treatment as surface dressings</i>	
EMULSION <ul style="list-style-type: none"> • Efflux 4 mm at 40°C - EN 12846-1 • Water effect on binder adhesion – EN 13614 • Breaking behaviour – EN 13075-1 	5-100 s (Class 5/6) ≥ 90 (Class 3) < 110-155 (Class 2/3)
RECOVERED BINDER <ul style="list-style-type: none"> • Penetration at 25°C - EN 1426 • Softening point – EN 1427 • Cohesion by pendulum – EN 13588 	≤ 220 (Class 5) ≥ 35°C (Class 8) ≥ 1.0 J/cm ² (Class 4)
STAGE 1 DURABILITY - STABILISED BINDER <ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	NPD NPD NPD
STAGE 2 DURABILITY - AGED BINDER <ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	≤ 220 (Class 5) NPD ≥ 1.0 J/cm ² (Class 4)
Dangerous regulated substances	NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C2 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

Surfix 80S C69BPF2/3

intended to be used for surface treatment as surface dressings