

## CE marking information – Colas Ltd



0836

**Colas Ltd, Wallage Lane, Rowfant  
West Sussex RH10 4NF**

13

C3 0836-CPR-13/F035

**EN 13808***Cationic bituminous emulsion***SLX-80 C69BPF3/4 C70BPF3/4***intended to be used for surface treatment as surface dressings***EMULSION**

- |  |                     |
|--|---------------------|
| • Efflux 4 mm at 40°C - EN 12846-1           | 5-100 s (Class 5/6) |
| • Water effect on binder adhesion – EN 13614 | ≥ 90 (Class 3)      |
| • Breaking behaviour – EN 13075-1            | 70-195 (Class 3/4)  |

**RECOVERED BINDER**

- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| • Penetration at 25°C - EN 1426   | ≤ 220 (Class 5)                   |
| • Softening point – EN 1427       | ≥ 43°C (Class 6)                  |
| • Cohesion by pendulum – EN 13588 | ≥ 1.2 J/cm <sup>2</sup> (Class 3) |

**STAGE 1 DURABILITY - STABILISED BINDER**

- |   |     |
|---|-----|
| • Durability of penetration at 25°C – EN 1426   | NPD |
| • Durability of softening point – EN 1427       | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NPD |

**STAGE 2 DURABILITY - AGED BINDER**

- |   |     |
|---|-----|
| • Durability of penetration at 25°C – EN 1426   | NPD |
| • Durability of softening point – EN 1427       | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NPD |

Dangerous regulated substances

NPD



0836

**Colas Ltd, Wallage Lane, Rowfant  
West Sussex RH10 4NF**

**13**

C3 0836-CPR-13/F035

***EN 13808***

*Cationic bituminous emulsion*

***SLX-80 C69BPF3/4 C70BPF3/4***

*intended to be used for surface treatment as surface dressings*