

CE marking information – Colas Ltd



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C5 0836-CPR-13/F035

EN 13808*Cationic bituminous emulsion***Premium 80 C70BPF2/3/4***intended to be used for surface treatment as surface dressings***EMULSION**

- Efflux 4 mm at 40°C - EN 12846-1 5-70 s (Class 5)
- Water effect on binder adhesion – EN 13614 ≥ 90 (Class 3)
- Breaking behaviour – EN 13075-1 < 110-195 (Class 2/3/4)

RECOVERED BINDER

- Penetration at 25°C - EN 1426 ≤ 220 (Class 5)
- Softening point – EN 1427 ≥ 46°C (Class 5)
- Cohesion by pendulum – EN 13588 ≥ 1.2 J/cm² (Class 3)

STAGE 1 DURABILITY - STABILISED BINDER

- Durability of penetration at 25°C – EN 1426 NPD
- Durability of softening point – EN 1427 NPD
- Durability of cohesion by pendulum – EN 13588 NPD

STAGE 2 DURABILITY - AGED BINDER

- Durability of penetration at 25°C – EN 1426 NPD
- Durability of softening point – EN 1427 NPD
- Durability of cohesion by pendulum – EN 13588 NPD

Dangerous regulated substances

NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C5 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

Premium 80 C70BPF2/3/4

intended to be used for surface treatment as surface dressings