

CE marking information – Colas Ltd



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C6 0836-CPR-13/F035

EN 13808*Cationic bituminous emulsion***Prinmuls MP90X C70BPF2/3/4***intended to be used for surface treatment as surface dressings***EMULSION**

- | | |
|--|---------------------|
| • Efflux 4 mm at 40°C - EN 12846-1 | 5-100 s (Class 5/6) |
| • Water effect on binder adhesion – EN 13614 | ≥ 90 (Class 3) |
| • Breaking behaviour – EN 13075-1 | ≤ 195 (Class 2/3/4) |

RECOVERED BINDER

- | | |
|-----------------------------------|-----------------------------------|
| • Penetration at 25°C - EN 1426 | ≤ 220 (Class 5) |
| • Softening point – EN 1427 | ≥ 50°C (Class 4) |
| • Cohesion by pendulum – EN 13588 | ≥ 1.4 J/cm ² (Class 2) |

STAGE 1 DURABILITY - STABILISED BINDER

- | | |
|---|-----|
| • Durability of penetration at 25°C – EN 1426 | NPD |
| • Durability of softening point – EN 1427 | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NPD |

STAGE 2 DURABILITY - AGED BINDER

- | | |
|---|-----------------------------------|
| • Durability of penetration at 25°C – EN 1426 | ≤ 150 (Class 4) |
| • Durability of softening point – EN 1427 | NPD |
| • Durability of cohesion by pendulum – EN 13588 | ≥ 1.4 J/cm ² (Class 2) |

Dangerous regulated substances

NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C6 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

Prinmuls MP90X C70BPF2/3/4

intended to be used for surface treatment as surface dressings