



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C13 0836-CPR-13/F035

EN 13808
Cationic bituminous emulsion

Leotak C40B
intended to be used for surface treatment as tack coat

EMULSION

- Efflux 2 mm at 40°C 15-70 s Class 3
- Water effect on binder adhesion – EN 13614 NR (Class 0)
- Breaking behaviour – EN 13075-1 NPD

RECOVERED BINDER

- Penetration at 25°C ≤ 220 (Class 5)
- Softening point – EN 1427 ≥ 39 (Class 7)
- Cohesion by pendulum – EN 13588 NR

STAGE 1 DURABILITY - STABILISED BINDER

- Durability of penetration at 25°C – EN 1426 NPD
- Durability of softening point – EN 1427 NPD
- Durability of cohesion by pendulum – EN 13588 NR

STAGE 2 DURABILITY - AGED BINDER

- Durability of penetration at 25°C – EN 1426 NPD
- Durability of softening point – EN 1427 NPD
- Durability of cohesion by pendulum – EN 13588 NR

Dangerous regulated substances

NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C13 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

Leotak C40B

intended to be used for surface treatment as tack coat