


CE marking information – Colas Ltd

 0836	
Colas Ltd, Wallage Lane, Rowfant West Sussex RH10 4NF 13 C14 0836-CPR-13/F035	
EN 13808 <i>Cationic bituminous emulsion</i> Leocatic Spray C55B3 <i>intended to be used for surface treatments as surface dressings or slurry systems (slurry seals and micro surfacing), tack coat, patching, repair of potholes, crack sealing, dust palliative, penetration, impregnation, plant mixed or mixed in place cold mixes (for base course, binder course or wearing course), cold recycling and more generally road construction and road maintenance</i>	
EMULSION	
<ul style="list-style-type: none"> • Efflux 2 mm at 40°C • Water effect on binder adhesion – EN 13614 • Breaking behaviour – EN 13075-1 	15-70 s Class 3 NR (Class 0) 70-155 (Class 3)
RECOVERED BINDER	
<ul style="list-style-type: none"> • Penetration at 25°C • Softening point – EN 1427 • Cohesion by pendulum – EN 13588 	≤ 220 (Class 5) ≥ 43 (Class 6) NR
STAGE 1 DURABILITY - STABILISED BINDER	
<ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	NPD NPD NR
STAGE 2 DURABILITY - AGED BINDER	
<ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	NPD NPD NR
Dangerous regulated substances	NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C14 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

Leocatic Spray C55B3

intended to be used for surface treatment as surface dressings or slurry systems (slurry seals and micro surfacing), tack coat, patching, repair of potholes, crack sealing, dust palliative, penetration, impregnation, plant mixed or mixed in place cold mixes (for base course, binder course or wearing course), cold recycling and more generally road construction and road maintenance