


## CE marking information – Colas Ltd

|  |  |
|--|--|
| <br><b>0836</b>   |  |
| <b>Colas Ltd, Wallage Lane, Rowfant<br/>West Sussex RH10 4NF</b><br><br><b>13</b><br><br>C23 0836-CPR-13/F035  |  |
| <b>EN 13808</b><br><i>Cationic bituminous emulsion</i><br><br><b>Patchmaster 100 C60B4/5</b><br><i>intended to be used for surface treatment as patching and repair of potholes</i>  |  |
| <b>EMULSION</b><br><ul style="list-style-type: none"> <li>• Efflux 2 mm at 40°C - EN 12846-1</li> <li>• Water effect on binder adhesion – EN 13614</li> <li>• Breaking behaviour – EN 13075-1</li> </ul>   | 15-70 s Class 3<br>≥ 90 (Class 3)<br>110- >170 (Class 4/5) |
| <b>RECOVERED BINDER</b><br><ul style="list-style-type: none"> <li>• Penetration at 25°C, 0.1 mm - EN 1426</li> <li>• Softening point, °C – EN 1427</li> <li>• Cohesion by pendulum – EN 13588</li> </ul>   | ≤ 150 (Class 4)<br>≥ 39 (Class 7)<br>NR                    |
| <b>STAGE 1 DURABILITY - STABILISED BINDER</b><br><ul style="list-style-type: none"> <li>• Durability of penetration at 25°C – EN 1426</li> <li>• Durability of softening point – EN 1427</li> <li>• Durability of cohesion by pendulum – EN 13588</li> </ul> | NPD<br>NPD<br>NR   |
| <b>STAGE 2 DURABILITY - AGED BINDER</b><br><ul style="list-style-type: none"> <li>• Durability of penetration at 25°C – EN 1426</li> <li>• Durability of softening point – EN 1427</li> <li>• Durability of cohesion by pendulum – EN 13588</li> </ul>       | NPD<br>NPD<br>NR   |
| Dangerous regulated substances   | NPD  |



0836

**Colas Ltd, Wallage Lane, Rowfant  
West Sussex RH10 4NF**

**13**

C23 0836-CPR-13/F035

***EN 13808***

*Cationic bituminous emulsion*

***Patchmaster 100 C60B4/5***

*intended to be used for surface treatment as patching and repair of potholes*