


CE marking information – Colas Ltd

 0836	
Colas Ltd, Wallage Lane, Rowfant West Sussex RH10 4NF 13 C24 0836-CPR-13/F035	
EN 13808 <i>Cationic bituminous emulsion</i> Patchmaster 200 C60BP4/5 <i>intended to be used for surface treatment as patching and repair of potholes</i>	
EMULSION	
• Efflux 2 mm at 40°C - EN 12846-1	15-70 s (Class 3)
• Water effect on binder adhesion – EN 13614	≥ 90 (Class 3)
• Breaking behaviour – EN 13075-1	110- >170 (Class 4/5)
RECOVERED BINDER	
• Penetration at 25°C - EN 1426	≤ (150 × 0.1) mm (Class 4)
• Softening point – EN 1427	≥ 50°C (Class 4)
• Cohesion by pendulum – EN 13588	≥ 0.7 J/cm ² (Class 5)
STAGE 1 DURABILITY - STABILISED BINDER	
• Durability of penetration at 25°C – EN 1426	NPD
• Durability of softening point – EN 1427	NPD
• Durability of cohesion by pendulum – EN 13588	NPD
STAGE 2 DURABILITY - AGED BINDER	
• Durability of penetration at 25°C – EN 1426	≤ (50 × 0.1) mm (Class 2)
• Durability of softening point – EN 1427	≥ 55°C (Class 3)
• Durability of cohesion by pendulum – EN 13588	≥ 0.7 J/cm ² (Class 5)
Dangerous regulated substances	NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C24 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

Patchmaster 200 C60BP4/5

intended to be used for surface treatment as patching and repair of potholes