

CE marking information – Colas Ltd

 0836	
Colas Ltd, Wallage Lane, Rowfant West Sussex RH10 4NF 13 C27 0836-CPR-13/F035	
EN 13808 <i>Cationic bituminous emulsion</i> RS Bitukold C60B3/4 C65B3/4 <i>intended to be used for surface treatment as joint sealing in road construction and road maintenance</i>	
EMULSION <ul style="list-style-type: none"> • Efflux 2 mm at 40°C - EN 12846-1 • Water effect on binder adhesion – EN 13614 • Breaking behaviour – EN 13075-1 	NR (Class 0) ≥ 90 (Class 3) 70-195 (Class 3/4)
RECOVERED BINDER <ul style="list-style-type: none"> • Penetration at 25°C - EN 1426 • Softening point – EN 1427 • Cohesion by pendulum – EN 13588 	≤ 150 (Class 4) ≥ 39 (Class 7) NR
STAGE 1 DURABILITY - STABILISED BINDER <ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	NPD NPD NR
STAGE 2 DURABILITY - AGED BINDER <ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	NPD NPD NR
Dangerous regulated substances	NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C27 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

RS Bitukold C60B3/4 C65B3/4

*intended to be used for surface treatment as joint sealing in road construction and
road maintenance*