



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

17

C16 0836-CPR-13/F035

EN 13808
Cationic bituminous emulsion

Colbond Multi – C70BP3
intended to be used for surface treatment as bond coat and sealing

EMULSION

- Efflux 4 mm at 40°C – EN 12846-1 5-70 s (Class 5)
- Water effect on binder adhesion – EN 13614 NR (Class 0)
- Breaking behaviour – EN 13075-1 70-155 (Class 3)

RECOVERED BINDER

- Penetration at 25°C, 0.1 mm – EN 1426 ≤ 100 (Class 3)
- Softening point, °C – EN 1427 ≥ 50 (Class 4)
- Cohesion by pendulum, J/cm² – EN 13588 ≥ 1.0 (Class 4)

STAGE 1 DURABILITY - STABILISED BINDER

- Durability of penetration at 25°C – EN 1426 NPD
- Durability of softening point – EN 1427 NPD
- Durability of cohesion by pendulum – EN 13588 NPD

STAGE 2 DURABILITY - AGED BINDER

- Durability of penetration at 25°C – EN 1426 ≤ 100 (Class 3)
- Durability of softening point – EN 1427 ≥ 50 (Class 4)
- Durability of cohesion by pendulum – EN 13588 ≥ 0.7 (Class 5)

Dangerous regulated substances	NPD
--------------------------------	-----



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

17

C16 0836-CPR-13/F035

EN 13808
Cationic bituminous emulsion

Colbond Multi – C70BP3

intended to be used for surface treatment as bond coat and sealing