

CE marking information – Colas Ltd



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C27/1 0836-CPR-13/F035

EN 13808*Cationic bituminous emulsion***RS Bitukold for RS Spray C60B3/4 C65B3/4**

*intended to be used for surface treatment as joint sealing in road construction and
road maintenance*

EMULSION

- | | |
|--|--------------------|
| • Efflux 2 mm at 40°C - EN 12846-1 | NR (Class 0) |
| • Water effect on binder adhesion – EN 13614 | ≥ 90 (Class 3) |
| • Breaking behaviour – EN 13075-1 | 70-195 (Class 3/4) |

RECOVERED BINDER

- | | |
|-----------------------------------|-----|
| • Penetration at 25°C - EN 1426 | NPD |
| • Softening point – EN 1427 | NPD |
| • Cohesion by pendulum – EN 13588 | NR |

STAGE 1 DURABILITY - STABILISED BINDER

- | | |
|---|-----|
| • Durability of penetration at 25°C – EN 1426 | NPD |
| • Durability of softening point – EN 1427 | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NR |

STAGE 2 DURABILITY - AGED BINDER

- | | |
|---|-----|
| • Durability of penetration at 25°C – EN 1426 | NPD |
| • Durability of softening point – EN 1427 | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NR |

Dangerous regulated substances

NPD