

# COLAS PRODUCTS DATA SHEET

## COLSPRAY



**Colspray** is a rapid setting, cold applied bitumen spray designed for sealing vertical joints. **Colspray** can also be used as a tack coat helping to prevent the ingress of water.

### WHERE TO USE?

- Transverse or longitudinal vertical joints
- Trench reinstatements
- Patch repairs
- Drain or manhole frames
- Kerb channels

### PREPARATION

**Colspray** should not be applied in ambient temperatures of less than 5°C. Ensure surface is clean and free from loose material, oil, grease, standing water and weeds.

### APPLICATION

Ensure that the surface is clean and free from loose materials, oil, grease, standing water and weeds.

### APPLICATION

Shake can vigorously before use. Turn can upside down and apply **Colspray** in even strokes with nozzle 200-300mm away from the surface to be treated. Ensure complete coverage. After use spray briefly with can in upright position to clear nozzle.

### COVERAGE

The coverage rate for **Colspray** should be 0.7 to 1.5 kg/m<sup>2</sup>, depending on the texture and porosity of the surface.

### PACKAGING

**Colspray** is supplied in 750ml aerosol cans (12 per pack).

### STORAGE

- Caution: pressurised container, protect from sunlight
- Do not pierce or burn even after use
- Do not expose to temperatures exceeding 50°C
- Do not spray on a naked flame or any incandescent material
- Keep out of reach of children

### STANDARDS

**Colspray** complies with BS 594987 Clause 6.9 Joints.

### SAFETY

For full safety information, please request the **Colspray** Safety Data Sheet 149 using the contact information below.

#### NATIONAL SALES OFFICE

Loushers Lane  
Warrington  
Cheshire  
WA4 6RZ  
T: 01925 632 616  
E: [product.sales@colas.co.uk](mailto:product.sales@colas.co.uk)



WE OPEN THE WAY