

**Declaration of Performance**

**DoP/CQ/A6204**

1	Unique identification of the product-type  <b>A6204</b> Carnsew Quarry		
2	Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)  <b>Hot Rolled Asphalt</b> <b>HRA 15/10 F surf 40/60 rec</b>		
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  <b>Bituminous Mixtures : Hot Rolled Asphalt : Surface Course</b>		
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):  <b>Colas Ltd, Rowfant, Crawley, West Sussex RH10 4NF</b>		
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  <b>Not Applicable</b>		
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:  <b>System 2+</b>		
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard: Notified factory production control certification body No. 0086 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control number 0086-CPD-590156.		
8	Not Applicable		
9	<b>Declared Performance</b>		
	Essential characteristics	Performance	Harmonised Technical Specification EN 13108-4: 2006
	1. Adhesion of binder to aggregate 2. Stiffness 3. Resistance to permanent deformation 4. Resistance to fatigue 5. Skid resistance 6. Resistance to abrasion 7. Reaction to Fire 8. Dangerous substances 9. Durability 10. Noise Absorption		
	2, 3, 4, 5, 9, 10	Target grading passing sieve Sieve (mm) 14 10 6.3 2 0.5 0.25 0.063	Passing (%) 100 95 83 79 71 42 12
	1, 2, 3, 4, 5, 6, 9, 10	Target binder content (%)	8.8
	1, 2, 3, 4, 5, 9, 10	Minimum void content	NPD
		Maximum void content	NPD
	2, 3, 4, 5, 9, 10	Maximum Voids filled with Bitumen	NPD
		Minimum Voids filled with Bitumen	NPD
		Minimum Voids in Mineral Aggregate	NPD
	3	Minimum Marshall Stability	NPD
		Maximum Marshall Stability	NPD
		Minimum Marshall Flow	NPD
		Maximum Marshall Flow	NPD
		Minimum MQ	NPD
		Maximum MQ	NPD
		Resistance to Permanent Deformation	NPD
	1, 9	Water sensitivity	NPD
	1, 2, 3, 4, 9	Minimum temperature (°C)	150
		Maximum Temperature (°C)	190
	2, 9	Minimum Stiffness	NPD
		Maximum Stiffness	NPD
	3, 9	Maximum creep rate	NPD
	4, 9	Resistance to fatigue	NPD
	6, 9	Resistance to abrasion	NPD
	7, 9	Reaction to Fire	NPD
	8, 9	Dangerous substances	NPD
	9	Mixture SATS durability index	NPD
	9	Low temperature property	NPD
	9	Fracture toughness	NPD
	9	Resistance to fuel for application on airfields	NPD
	9	Resistance to de-icing fluids for application on airfields	NPD
	1, 4	Binder Drainage	NPD
10	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.		
	Signed for and on behalf of the manufacturer by:		
	Name & Function	Carl Fergusson	Director - Airports, Asphalt & projects
	Place & Date of Issue	Carnsew Quarry	07 July 2014
	Signature		