


**Declaration of Performance**

**DoP/CQ/M5221**

|    |   |   |   |
|----|---|---|---|
| 1  | Unique identification of the product-type<br><br><b>M5221</b><br>Carnsew Quarry   |   |   |
| 2  | Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)<br><br><b>Asphaltic Concrete</b><br><b>AC 32 dense base 40/60 rec</b>   |   |   |
| 3  | Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:<br><br><b>Bituminous Mixtures : Asphaltic Concrete : Base</b>  |   |   |
| 4  | Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):<br><br><b>Colas Ltd, Rowfant, Crawley, West Sussex RH10 4NF</b>   |   |   |
| 5  | Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):<br><br><b>Not Applicable</b>   |   |   |
| 6  | System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:<br><br><b>System 2+</b>  |   |   |
| 7  | In case of the declaration of performance concerning a construction product covered by a harmonised standard: Notified factory production control certification body No. 0086 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control number 0086-CPD-590156. |   |   |
| 8  | Not Applicable  |   |   |
| 9  | <b>Declared Performance</b>   |   |   |
|    | Essential characteristics   | Performance   | Harmonised Technical Specification EN 13108-1: 2006 |
|    | 1. Adhesion of binder to aggregate<br>2. Stiffness<br>3. Resistance to permanent deformation<br>4. Resistance to fatigue<br>5. Skid resistance<br>6. Resistance to abrasion<br>7. Reaction to Fire<br>8. Dangerous substances<br>9. Durability<br>10. Noise Absorption  |   |   |
|    | 2, 3, 4, 5, 9, 10   | Target grading passing sieve<br>Sieve (mm)                      Passing (%)<br>40                                      100<br>31.5                                    99<br>20                                       86<br>6.3                                      52<br>2    32<br>0.25                                    11<br>0.063                                  6 | EN 12697-1: 2012                                    |
|    | 1, 2, 3, 4, 5, 6, 9, 10   | Target binder content (%)                      4  | EN 12697-2: 2002                                    |
|    | 1, 2, 3, 4, 5, 9, 10  | Minimum void content                          NPD   | EN 12697-8: 2003                                    |
|    |   | Maximum void content                          NPD   | EN 12697-8: 2003                                    |
|    | 2, 3, 4, 5, 9, 10   | Maximum Voids filled with Bitumen                      NPD  | EN 12697-8: 2003                                    |
|    |   | Minimum Voids filled with Bitumen                      NPD  | EN 12697-8: 2003                                    |
|    |   | Minimum Voids in Mineral Aggregate                      NPD   | EN 12697-8: 2003                                    |
|    | 3   | Minimum Marshall Stability                          NPD   | EN 12697-34: 2012                                   |
|    |   | Maximum Marshall Stability                          NPD   | EN 12697-34: 2012                                   |
|    |   | Minimum Marshall Flow                                  NPD  | EN 12697-34: 2012                                   |
|    |   | Maximum Marshall Flow                                  NPD  | EN 12697-34: 2012                                   |
|    |   | Minimum MQ    NPD   | EN 12697-34: 2012                                   |
|    |   | Maximum MQ    NPD   | EN 12697-34: 2012                                   |
|    |   | Resistance to Permanent Deformation                      NPD  | EN 12697-22: 2003                                   |
|    | 1, 9  | Water sensitivity    NPD  | EN 12697-12: 2008                                   |
|    | 1, 2, 3, 4, 9   | Minimum Temperature (°C)                                  150   | EN 12697-13: 2000                                   |
|    |   | Maximum Temperature (°C)                                  190   | EN 12697-13: 2000                                   |
|    | 2, 9  | Minimum Stiffness    NPD  | EN 12697-26: 2012                                   |
|    |   | Maximum Stiffness    NPD  | EN 12697-26: 2012                                   |
|    | 3, 9  | Maximum creep rate    NPD   | EN 12697-25: 2005                                   |
|    | 4, 9  | Resistance to fatigue    NPD  | EN 12697-24: 2012                                   |
|    | 6, 9  | Resistance to abrasion    NPD   | EN 12697-16: 2004                                   |
|    | 7, 9  | Reaction to Fire    NPD   | EN ISO 11925-2                                      |
|    | 8, 9  | Dangerous substances    NPD   | As required   |
|    | 9   | Mixture SATS durability index                                  NPD  | EN 12697-45: 2012                                   |
|    | 9   | Low temperature property    NPD   | EN 12697-46: 2012                                   |
|    | 9   | Fracture toughness    NPD   | EN 12697-44: 2010                                   |
|    | 9   | Resistance to fuel for application on airfields                      NPD  | EN 12697-43: 2005                                   |
|    | 9   | Resistance to de-icing fluids for application on airfields                      NPD   | EN 12697-41: 2005                                   |
|    | 1, 4  | Binder Drainage    NPD  | EN 12697-18: 2004                                   |
| 10 | The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.   |   |   |
|    | Signed for and on behalf of the manufacturer by:  |   |   |
|    | Name & Function   | Carl Fergusson  | Director - Airports, Asphalt & projects             |
|    | Place & Date of Issue   | Carnsew Quarry  | 10 October 2014                                     |
|    | Signature   |    |   |