Declaration of Performance DoP/CQ/M7410

| | | · · · · · · · · · · · · · · · · · · · | | | |
|------------------------|--|---|--------------------------|--|--|
| 1 | Unique identification of the product-type | | | | |
| | M7410 | | | | |
| | Carnsew Quarry | | | | |
| 2 | Type, batch or serial number o | Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) | | | |
| | Asphaltic Concrete | | | | |
| | | · | V60 | | |
| _ | AC 10 close surf 160/220 PSV60 | | | | |
| 3 | Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the | | | | |
| | manufacturer: Bituminous Mixtures : Asphaltic Concrete : Surface Course | | | | |
| | | | | | |
| 4 | Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): | | | | |
| | | • | | | |
| - | Colas Ltd, Rowfant, Crawley, West Sussex RH10 4NF | | | | |
| 5 | Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): | | | | |
| | | | | | |
| | Not Applicable | | | | |
| 6 | System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: | | | | |
| | | | | | |
| | System 2+ | | | | |
| | | | | | |
| 7 | In case of the declaration of performance concerning a construction product covered by a harmonised standard: Notified factory production | | | | |
| | control certification body No. 0086 | b performed the initial inspection of the manufact | uring plant and of facto | ry production control and the | |
| | continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory | | | | |
| | production control number 0086-CPD-590156. | | | | |
| 8 | Not Applicable | | | | |
| | ** | | | | |
| 9 Declared Performance | | | | Hamman III I a la cara a man | |
| | Essential characteristics | Performance | | Harmonised Technical Specification EN 13108-1: 2006 | |
| | Adhesion of binder to aggregate | | | _5355 1. 2555 | |
| | 2. Stiffness | | | | |
| | 3. Resistance to permanent deformation | | | | |
| | 4. Resistance to fatigue | | | | |
| | 5. Skid resistance | | | | |
| | 6. Resistance to abrasion | | | | |
| | 7. Reaction to Fire | | | | |
| | 8. Dangerous substances | | | | |
| | 9. Durability | | | | |
| | 10. Noise Absorption | | | | |
| | 2, 3, 4, 5, 9, 10 | Target grading passing sieve | | EN 12697-1: 2012 | |
| | | Sieve (mm) | Passing (%) | | |
| | | 14 10 | 100 98 | | |
| | | 6.3 | 98 67 | | |
| | | 2 | 28 | | |
| | | 1 | 20 | | |
| | | 0.063 | 6 | | |
| | 1, 2, 3, 4, 5, 6, 9, 10 | Target binder content (%) | 5.7 | EN 12697-2: 2002 | |
| | 1, 2, 3, 4, 5, 9, 10 | Minimum void content | NPD | EN 12697-8: 2003 | |
| | | Maximum void content | NPD | EN 12697-8: 2003 | |
| | 2, 3, 4, 5, 9, 10 | Maximum Voids filled with Bitumen | NPD | EN 12697-8: 2003 | |
| | | Minimum Voids filled with Bitumen | NPD | EN 12697-8: 2003 | |
| | | Minimum Voids in Mineral Aggregate | NPD | EN 12697-8: 2003 | |
| | 3 | Minimum Marshall Stability Maximum Marshall Stability | NPD NPD | EN 12697-34: 2012 EN 12697-34: 2012 | |
| | | Maximum Marshall Stability Minimum Marshall Flow | NPD NPD | EN 12697-34: 2012 EN 12697-34: 2012 | |
| | | Maximum Marshall Flow | NPD | EN 12697-34: 2012 | |
| | | Minimum MQ | NPD | EN 12697-34: 2012 | |
| | | Maximum MQ | NPD | EN 12697-34: 2012 | |
| | | Resistance to Permananet Deformation | NPD | EN 12697-22: 2003 | |
| | 1, 9 | Water sensitivity | NPD | EN 12697-12: 2008 | |
| | 1, 2, 3, 4, 9 | Minimum temperature (°C) | 130 | EN 12697-13: 2000 | |
| | | Maximum Temperature (°C) | 170 | EN 12697-13: 2000 | |
| | 2,9 | Minimum Stiffness | NPD | EN 12697-26: 2012 | |
| | 3.0 | Maximum Stiffness | NPD | EN 12697-26: 2012 | |
| | 3, 9 4. 9 | Maximum creep rate Resistance to fatigue | NPD NPD | EN 12697-25: 2005 EN 12697-24: 2012 | |
| | 6,9 | Resistance to tangue Resistance to abrasion | NPD | EN 12697-16: 2004 | |
| | 7,9 | Reaction to Fire | NPD | EN ISO 11925-2 | |
| | 8, 9 | Dangerous substances | NPD | As required | |
| | 9 | Mixture SATS durability index | NPD | EN 12697-45: 2012 | |
| | 9 | Low temperature property | NPD | EN 12697-46: 2012 | |
| | 9 | Fracture toughness | NPD | EN 12697-44: 2010 | |
| | 9 | Resistance to fuel for application on airfields | NPD | EN 12697-43: 2005 | |
| | 9 | Resistance to de-icing fluids for application on airfields | NPD | EN 12697-41: 2005 | |
| 10 | 1, 4 | Binder Drainage | NPD | EN 12697-18: 2004 | |
| 10 | The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of | | | | |
| | performance is issued under the sole responsibility of the manufacturer identified in point 4. | | | | |
| | Signed for and on behalf of the manufacturer by: | | | | |
| | • | | | | |
| | Name & Function | Carl Fergusson | • | rispinui a projecis | |
| | Place & Date of Issue | Carnsew Quarry | 29 August 2014 | | |
| | Signature | Dogwa | | | |
| | 3-10-10-0 | (JUNY) 1- | | | |