

Declaration of Performance

DoP/CQ/M7417

1	Unique identification of the product-type M7417 Carnsew Quarry		
2	Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) Asphaltic Concrete AC 10 close surf 40/60		
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Bituminous Mixtures : Asphaltic Concrete : Surface Course		
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): Colas Ltd, Rowfant, Crawley, West Sussex RH10 4NF		
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): Not Applicable		
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: System 2+		
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard: Notified factory production control certification body No. 0086 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control number 0086-CPD-590156.		
8	Not Applicable		
9	Declared Performance		
	Essential characteristics	Performance	Harmonised Technical Specification EN 13108-1: 2006
	1. Adhesion of binder to aggregate 2. Stiffness 3. Resistance to permanent deformation 4. Resistance to fatigue 5. Skid resistance 6. Resistance to abrasion 7. Reaction to Fire 8. Dangerous substances 9. Durability 10. Noise Absorption		
	2, 3, 4, 5, 9, 10	Target grading passing sieve Sieve (mm) Passing (%) 14 100 10 98 6.3 67 2 28 1 20 0.063 6	EN 12697-1: 2012
	1, 2, 3, 4, 5, 6, 9, 10	Target binder content (%) 5.7	EN 12697-2: 2002
	1, 2, 3, 4, 5, 9, 10	Minimum void content NPD	EN 12697-8: 2003
		Maximum void content NPD	EN 12697-8: 2003
	2, 3, 4, 5, 9, 10	Maximum Voids filled with Bitumen NPD	EN 12697-8: 2003
		Minimum Voids filled with Bitumen NPD	EN 12697-8: 2003
		Minimum Voids in Mineral Aggregate NPD	EN 12697-8: 2003
	3	Minimum Marshall Stability NPD	EN 12697-34: 2012
		Maximum Marshall Stability NPD	EN 12697-34: 2012
		Minimum Marshall Flow NPD	EN 12697-34: 2012
		Maximum Marshall Flow NPD	EN 12697-34: 2012
		Minimum MQ NPD	EN 12697-34: 2012
		Maximum MQ NPD	EN 12697-34: 2012
		Resistance to Permanent Deformation NPD	EN 12697-22: 2003
	1, 9	Water sensitivity NPD	EN 12697-12: 2008
	1, 2, 3, 4, 9	Minimum temperature (°C) 150	EN 12697-13: 2000
		Maximum Temperature (°C) 190	EN 12697-13: 2000
	2, 9	Minimum Stiffness NPD	EN 12697-26: 2012
		Maximum Stiffness NPD	EN 12697-26: 2012
	3, 9	Maximum creep rate NPD	EN 12697-25: 2005
	4, 9	Resistance to fatigue NPD	EN 12697-24: 2012
	6, 9	Resistance to abrasion NPD	EN 12697-16: 2004
	7, 9	Reaction to Fire NPD	EN ISO 11925-2
	8, 9	Dangerous substances NPD	As required
	9	Mixture SATS durability index NPD	EN 12697-45: 2012
	9	Low temperature property NPD	EN 12697-46: 2012
	9	Fracture toughness NPD	EN 12697-44: 2010
	9	Resistance to fuel for application on airfields NPD	EN 12697-43: 2005
	9	Resistance to de-icing fluids for application on airfields NPD	EN 12697-41: 2005
	1, 4	Binder Drainage NPD	EN 12697-18: 2004
10	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.		
	Signed for and on behalf of the manufacturer by:		
	Name & Function	Carl Fergusson	Director - Airports, Asphalt & projects
	Place & Date of Issue	Carnsew Quarry	29 August 2014
	Signature		