

Declaration of Performance

DoP/CQ/13043/32C

1	Unique identification of the product-type <p align="center">32C Carnsew Quarry</p>																																																																		
2	Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) <p align="center">Aggregate 20/31.5mm</p>																																																																		
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: <p align="center">Aggregates for Bituminous Mixtures and Surface Treatments for Roads, Airfields and other trafficked areas</p>																																																																		
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): <p align="center">Colas Ltd, Rowfant, Crawley, West Sussex RH10 4NF</p>																																																																		
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): <p align="center">Not Applicable</p>																																																																		
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: <p align="center">System 4</p>																																																																		
7	Not Applicable																																																																		
8	Not Applicable																																																																		
9	<table border="1"> <thead> <tr> <th>Essential characteristics</th> <th>Performance</th> <th>Harmonised Technical Specification EN 13043:2013</th> </tr> </thead> <tbody> <tr> <td rowspan="6">1. Particle shape, size and density</td> <td>Aggregate Size</td> <td>20/31.5mm EN 933-1: 2012</td> </tr> <tr> <td>Grading</td> <td>GC85/35 EN 933-1: 2012</td> </tr> <tr> <td>Shape of Coarse Aggregate</td> <td>FL35 EN 933-3: 2012</td> </tr> <tr> <td>Particle Density</td> <td>2.67 Mg/m³ EN 1097-6: 2000</td> </tr> <tr> <td>Water Absorption</td> <td>WA242 EN 1097-6: 2000</td> </tr> <tr> <td>Fines Content</td> <td>F4 EN 933-1: 2012</td> </tr> <tr> <td>2. Cleanliness</td> <td>Fines Quality</td> <td>NPD EN 933-9: 2013</td> </tr> <tr> <td>3. Percentage of crushed and broken surfaces</td> <td>Percentage of crushed particles / broken surfaces</td> <td>NPD EN 933-5: 1998</td> </tr> <tr> <td>4. Affinity to bituminous binders</td> <td>Affinity to bituminous binders</td> <td>NPD EN 12697-11: 2012</td> </tr> <tr> <td>5. Resistance to fragmentation/crushing</td> <td>Resistance to fragmentation</td> <td>LA30 EN 1097-2: 2010</td> </tr> <tr> <td rowspan="3">6. Resistance polishing/abrasion/wear/attrition</td> <td>Polished Stone Value</td> <td>PSV95 EN 1097-8: 2009</td> </tr> <tr> <td>Aggregate Abrasion Value</td> <td>AAV10 EN 1097-8: 2009</td> </tr> <tr> <td>Resistance to wear of coarse aggregate</td> <td>NPD EN 1097-1: 2011</td> </tr> <tr> <td>7. Resistance to thermal shock</td> <td>Resistance to thermal shock</td> <td>NPD EN 1367-5: 2011</td> </tr> <tr> <td rowspan="3">8. Volume stability</td> <td>Dicalcium silicate disintegration of air cooled blast furnace slag</td> <td>NPD EN 1744-1: 2012</td> </tr> <tr> <td>Iron disintegration of air cooled blast furnace slag</td> <td>NPD EN 1744-1: 2012</td> </tr> <tr> <td>Volume stability of steel slag</td> <td>NPD EN 1744-1: 2012</td> </tr> <tr> <td>9. Composition/content</td> <td>Composition / content</td> <td>Granite EN 932-3: 1997</td> </tr> <tr> <td rowspan="4">10. Dangerous substances</td> <td>Emission of radioactivity</td> <td>NPD As required</td> </tr> <tr> <td>Release of heavy metals</td> <td>NPD As required</td> </tr> <tr> <td>Release of polyaromatic carbons</td> <td>NPD As required</td> </tr> <tr> <td>Release of other dangerous substances</td> <td>NPD As required</td> </tr> <tr> <td>11. Durability against freeze-thaw</td> <td>Durability against freeze / thaw</td> <td>MS18 EN 1367-1: 2007/EN 1367-2: 2009</td> </tr> <tr> <td>12. Durability against weathering</td> <td>Durability against weathering</td> <td>NPD EN 1367-3: 2001</td> </tr> <tr> <td>13. Durability against studded tyres</td> <td>Durability against studded tyres</td> <td>NPD EN 1097-9: 1998</td> </tr> </tbody> </table>	Essential characteristics	Performance	Harmonised Technical Specification EN 13043:2013	1. Particle shape, size and density	Aggregate Size	20/31.5mm EN 933-1: 2012	Grading	GC85/35 EN 933-1: 2012	Shape of Coarse Aggregate	FL35 EN 933-3: 2012	Particle Density	2.67 Mg/m ³ EN 1097-6: 2000	Water Absorption	WA242 EN 1097-6: 2000	Fines Content	F4 EN 933-1: 2012	2. Cleanliness	Fines Quality	NPD EN 933-9: 2013	3. Percentage of crushed and broken surfaces	Percentage of crushed particles / broken surfaces	NPD EN 933-5: 1998	4. Affinity to bituminous binders	Affinity to bituminous binders	NPD EN 12697-11: 2012	5. Resistance to fragmentation/crushing	Resistance to fragmentation	LA30 EN 1097-2: 2010	6. Resistance polishing/abrasion/wear/attrition	Polished Stone Value	PSV95 EN 1097-8: 2009	Aggregate Abrasion Value	AAV10 EN 1097-8: 2009	Resistance to wear of coarse aggregate	NPD EN 1097-1: 2011	7. Resistance to thermal shock	Resistance to thermal shock	NPD EN 1367-5: 2011	8. Volume stability	Dicalcium silicate disintegration of air cooled blast furnace slag	NPD EN 1744-1: 2012	Iron disintegration of air cooled blast furnace slag	NPD EN 1744-1: 2012	Volume stability of steel slag	NPD EN 1744-1: 2012	9. Composition/content	Composition / content	Granite EN 932-3: 1997	10. Dangerous substances	Emission of radioactivity	NPD As required	Release of heavy metals	NPD As required	Release of polyaromatic carbons	NPD As required	Release of other dangerous substances	NPD As required	11. Durability against freeze-thaw	Durability against freeze / thaw	MS18 EN 1367-1: 2007/EN 1367-2: 2009	12. Durability against weathering	Durability against weathering	NPD EN 1367-3: 2001	13. Durability against studded tyres	Durability against studded tyres	NPD EN 1097-9: 1998
Essential characteristics	Performance	Harmonised Technical Specification EN 13043:2013																																																																	
1. Particle shape, size and density	Aggregate Size	20/31.5mm EN 933-1: 2012																																																																	
	Grading	GC85/35 EN 933-1: 2012																																																																	
	Shape of Coarse Aggregate	FL35 EN 933-3: 2012																																																																	
	Particle Density	2.67 Mg/m ³ EN 1097-6: 2000																																																																	
	Water Absorption	WA242 EN 1097-6: 2000																																																																	
	Fines Content	F4 EN 933-1: 2012																																																																	
2. Cleanliness	Fines Quality	NPD EN 933-9: 2013																																																																	
3. Percentage of crushed and broken surfaces	Percentage of crushed particles / broken surfaces	NPD EN 933-5: 1998																																																																	
4. Affinity to bituminous binders	Affinity to bituminous binders	NPD EN 12697-11: 2012																																																																	
5. Resistance to fragmentation/crushing	Resistance to fragmentation	LA30 EN 1097-2: 2010																																																																	
6. Resistance polishing/abrasion/wear/attrition	Polished Stone Value	PSV95 EN 1097-8: 2009																																																																	
	Aggregate Abrasion Value	AAV10 EN 1097-8: 2009																																																																	
	Resistance to wear of coarse aggregate	NPD EN 1097-1: 2011																																																																	
7. Resistance to thermal shock	Resistance to thermal shock	NPD EN 1367-5: 2011																																																																	
8. Volume stability	Dicalcium silicate disintegration of air cooled blast furnace slag	NPD EN 1744-1: 2012																																																																	
	Iron disintegration of air cooled blast furnace slag	NPD EN 1744-1: 2012																																																																	
	Volume stability of steel slag	NPD EN 1744-1: 2012																																																																	
9. Composition/content	Composition / content	Granite EN 932-3: 1997																																																																	
10. Dangerous substances	Emission of radioactivity	NPD As required																																																																	
	Release of heavy metals	NPD As required																																																																	
	Release of polyaromatic carbons	NPD As required																																																																	
	Release of other dangerous substances	NPD As required																																																																	
11. Durability against freeze-thaw	Durability against freeze / thaw	MS18 EN 1367-1: 2007/EN 1367-2: 2009																																																																	
12. Durability against weathering	Durability against weathering	NPD EN 1367-3: 2001																																																																	
13. Durability against studded tyres	Durability against studded tyres	NPD EN 1097-9: 1998																																																																	
10	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.																																																																		
Signed for and on behalf of the manufacturer by:																																																																			
Name & Function	Carl Fergusson Director - Airports, Asphalt & projects																																																																		
Place & Date of Issue	Carnsew Quarry 08 July 2014																																																																		
Signature																																																																			