

## CE marking information – Colas Ltd



0836

**Colas Ltd, Wallage Lane, Rowfant  
West Sussex RH10 4NF**

**13**

C9/2 0836-CPR-13/F035

**EN 13808***Cationic bituminous emulsion****Cationic Slurry Seal - C55B(F) C60B(F)***

*intended to be used for surface treatment as slurry systems  
(slurry seals and micro surfacing)*

**EMULSION**

- |  |                 |
|--|-----------------|
| • Efflux 2 mm at 40°C                        | 15-70 s Class 3 |
| • Water effect on binder adhesion – EN 13614 | NR (Class 0)    |
| • Breaking behaviour – EN 13075-1            | NPD             |

**RECOVERED BINDER**

- |                                   |                 |
|-----------------------------------|-----------------|
| • Penetration at 25°C             | ≤ 330 (Class 7) |
| • Softening point – EN 1427       | ≥ 35 (Class 8)  |
| • Cohesion by pendulum – EN 13588 | NR              |

**STAGE 1 DURABILITY - STABILISED BINDER**

- |   |     |
|---|-----|
| • Durability of penetration at 25°C – EN 1426   | NPD |
| • Durability of softening point – EN 1427       | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NR  |

**STAGE 2 DURABILITY - AGED BINDER**

- |   |                 |
|---|-----------------|
| • Durability of penetration at 25°C – EN 1426   | ≤ 330 (Class 7) |
| • Durability of softening point – EN 1427       | ≥ 35 (Class 8)  |
| • Durability of cohesion by pendulum – EN 13588 | NR              |

Dangerous regulated substances

NPD



0836

**Colas Ltd, Wallage Lane, Rowfant  
West Sussex RH10 4NF**

**13**

C9/2 0836-CPR-13/F035

***EN 13808***

*Cationic bituminous emulsion*

***Cationic Slurry Seal - C55B(F) C60B(F)***

*intended to be used for surface treatment as slurry systems  
(slurry seals and micro surfacing)*