


CE marking information – Colas Ltd

 0836	
Colas Ltd, Wallage Lane, Rowfant West Sussex RH10 4NF 13 C24 0836-CPR-13/F035	
EN 13808 <i>Cationic bituminous emulsion</i> Patchmaster 200 C60BP3/4/5 <i>intended to be used for surface treatment as patching and repair of potholes</i>	
EMULSION	
<ul style="list-style-type: none"> • Efflux 2 mm at 40°C - EN 12846-1 • Water effect on binder adhesion – EN 13614 • Breaking behaviour – EN 13075-1 	15-70 s (Class 3) ≥ 90 (Class 3) 70 - >170 (Class 3/4/5)
RECOVERED BINDER	
<ul style="list-style-type: none"> • Penetration at 25°C - EN 1426 • Softening point – EN 1427 • Cohesion by pendulum – EN 13588 	≤ (150 × 0.1) mm (Class 4) ≥ 43°C (Class 6) ≥ 1.0 J/cm ² (Class 4)
STAGE 1 DURABILITY - STABILISED BINDER	
<ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	NPD NPD NPD
STAGE 2 DURABILITY - AGED BINDER	
<ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	≤ (50 × 0.1) mm (Class 2) ≥ 55°C (Class 3) ≥ 0.7 J/cm ² (Class 5)
Dangerous regulated substances	NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C24 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

Patchmaster 200 C60BP3/4/5

intended to be used for surface treatment as patching and repair of potholes