

## CE marking information – Colas Ltd



0836

**Colas Ltd, Wallage Lane, Rowfant  
West Sussex RH10 4NF**

**13**

C29 0836-CPR-13/F035

**EN 13808***Cationic bituminous emulsion***Leochip VLS - C67B***intended to be used for surface treatment as surface dressings***EMULSION**

- |  |   |
|--|---|
| • Dynamic viscosity at 40°C - EN 13302       | Min. 8000 mPa.s (0.005s <sup>-1</sup> )<br>or Max. 1200 mPa.s (1s <sup>-1</sup> ) |
| • Water effect on binder adhesion – EN 13614 | ≥ 90 (Class 3)  |
| • Breaking behaviour – EN 13075-1            | NPD   |

**RECOVERED BINDER**

- |                                   |                 |
|-----------------------------------|-----------------|
| • Penetration at 25°C             | ≤ 220 (Class 5) |
| • Softening point – EN 1427       | ≥ 35 (Class 8)  |
| • Cohesion by pendulum – EN 13588 | NR              |

**STAGE 1 DURABILITY - STABILISED BINDER**

- |   |     |
|---|-----|
| • Durability of penetration at 25°C – EN 1426   | NPD |
| • Durability of softening point – EN 1427       | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NR  |

**STAGE 2 DURABILITY - AGED BINDER**

- |   |                 |
|---|-----------------|
| • Durability of penetration at 25°C – EN 1426   | ≤ 220 (Class 5) |
| • Durability of softening point – EN 1427       | ≥ 35 (Class 8)  |
| • Durability of cohesion by pendulum – EN 13588 | NR              |

Dangerous regulated substances

NPD



0836

**Colas Ltd, Wallage Lane, Rowfant  
West Sussex RH10 4NF**

**13**

C29 0836-CPR-13/F035

***EN 13808***

*Cationic bituminous emulsion*

***Leochip VLS - C67B***

*intended to be used for surface treatment as surface dressings*