

CE marking information – Colas Ltd



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

17

C16 0836-CPR-13/F035

EN 13808*Cationic bituminous emulsion***Colbond Multi – C70BP2/3/4***intended to be used for surface treatment as bond coat and sealing***EMULSION**

- | | |
|--|------------------|
| • Efflux 4 mm at 40°C – EN 12846-1 | 5-70 s (Class 5) |
| • Water effect on binder adhesion – EN 13614 | NR (Class 0) |
| • Breaking behaviour – EN 13075-1 | 70-155 (Class 3) |

RECOVERED BINDER

- | | |
|--|-----------------|
| • Penetration at 25°C, 0.1 mm – EN 1426 | ≤ 100 (Class 3) |
| • Softening point, °C – EN 1427 | ≥ 50 (Class 4) |
| • Cohesion by pendulum, J/cm ² – EN 13588 | ≥ 1.0 (Class 4) |

STAGE 1 DURABILITY - STABILISED BINDER

- | | |
|---|-----|
| • Durability of penetration at 25°C – EN 1426 | NPD |
| • Durability of softening point – EN 1427 | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NPD |

STAGE 2 DURABILITY - AGED BINDER

- | | |
|---|-----------------|
| • Durability of penetration at 25°C – EN 1426 | ≤ 100 (Class 3) |
| • Durability of softening point – EN 1427 | ≥ 50 (Class 4) |
| • Durability of cohesion by pendulum – EN 13588 | ≥ 0.7 (Class 5) |

Dangerous regulated substances

NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

17

C16 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

Colbond Multi – C70BP2/3/4

intended to be used for surface treatment as bond coat and sealing