

CE marking information – Colas Ltd



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C10/2 0836-CPR-13/F035

EN 13808*Cationic bituminous emulsion****Cationic Slurry Seal Slow Set - C55B C60B***

*intended to be used for surface treatment as slurry systems
(slurry seals and micro surfacing)*

EMULSION

- | | |
|--|-----------------|
| • Efflux 2 mm at 40°C | 15-70 s Class 3 |
| • Water effect on binder adhesion – EN 13614 | NR (Class 0) |
| • Breaking behaviour – EN 13075-1 | NPD |

RECOVERED BINDER

- | | |
|-----------------------------------|-----------------|
| • Penetration at 25°C | ≤ 220 (Class 5) |
| • Softening point – EN 1427 | ≥ 39 (Class 7) |
| • Cohesion by pendulum – EN 13588 | NR |

STAGE 1 DURABILITY - STABILISED BINDER

- | | |
|---|-----|
| • Durability of penetration at 25°C – EN 1426 | NPD |
| • Durability of softening point – EN 1427 | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NR |

STAGE 2 DURABILITY - AGED BINDER

- | | |
|---|-----------------|
| • Durability of penetration at 25°C – EN 1426 | ≤ 220 (Class 5) |
| • Durability of softening point – EN 1427 | ≥ 39 (Class 7) |
| • Durability of cohesion by pendulum – EN 13588 | NR |

Dangerous regulated substances

NPD



0836

**Colas Ltd, Wallage Lane, Rowfant
West Sussex RH10 4NF**

13

C10/2 0836-CPR-13/F035

EN 13808

Cationic bituminous emulsion

Cationic Slurry Seal Slow Set - C55B C60B

*intended to be used for surface treatment as slurry systems
(slurry seals and micro surfacing)*