

COLAS PRODUCTS DATA SHEET

SECURE CHIP



Secure Chip is a spray applied emulsion binder for application to recently completed surface dressings.

Secure Chip is designed to reduce the amount of post sweeping required by securing the dressing aggregate in the mosaic structure minimising the risk of damaged windscreens from chippings dislodged by passing vehicles. Application of **Secure Chip** also gives a pleasing aesthetic and long lasting black colour resembling an asphalt surface.

The low application rate of **Secure Chip** results in the rapid breaking of the emulsion meaning that sites can be opened to traffic quickly minimising any disruption to local residents.

WHERE TO USE?

➤ On recently surface dressed road

PREPARATION

Secure Chip should be applied to recently applied surface dressings that have been swept.

APPLICATION

Secure Chip should be machine spray applied to recent surface dressing, after an initial sweeping of the site, at a temperature of 85°C.

COVERAGE

Secure Chip should be applied at spread rate of 0.2-0.4L/m².

PACKAGING

Secure Chip is supplied in bulk loads.

STORAGE

Secure Chip should be stored at 80-85°C in purpose build bulk storage tanks or spray tankers. For further information please refer to the Road Emulsion Association Code for Good Practice for the use and safety of Mobile Storage Tanks.

STANDARDS

Secure Chip complies with BS EN 13808:2013 C50BP3/4.

SAFETY

For full safety information please request the **Secure Chip** Safety Data Sheet 156S using the contact information below.

NATIONAL SALES OFFICE

Loushers Lane
Warrington
Cheshire
WA4 6RZ
T: 01925 632 616
E: product.sales@colas.co.uk



WE OPEN THE WAY