



Declaration of Performance

Cationic Bituminous Emulsion

No. C27

Manufacturer

Colas Ltd, 6210 Bishops Court, Birmingham Business Park, Solihull Parkway, Birmingham B37 7YB

Location

Warrington Works, Loushers Lane, Warrington, Cheshire, WA4 6RZ

Product description

Cationic bitumen emulsion for use as coating in the preparation of asphalt pavement joints

Additional information

RS Bitukold is bitumen emulsion for cold application to vertical joints in the construction of asphalt pavement layers. It may be brushed, poured or sprayed. Storage life is up to six months in sealed buckets protected from frost and extreme heat.

The construction product described conforms to the requirements provided below

Annex ZA of BS EN 13808:2013 – AVCP system 2+

No. of Certificate of Factory Production Control

UK 0836-CPR-13/F035

Declared performance

Characteristic	Category	Specification
EMULSION <ul style="list-style-type: none">Efflux 2 mm at 40°CBreaking behaviour	NR (Class 0) 70-195 (Class 3/4)	EN 13808 – Table 2 EN 12846-1 EN 13075-1
RECOVERED BINDER <ul style="list-style-type: none">Penetration at 25°C, 0.1 mmSoftening point, °CCohesion by pendulum	≤ 150 (Class 4) ≥ 39 (Class 7) NR	EN 13074-1 EN 1426 EN 1427 EN 13588
STAGE 1 DURABILITY - STABILISED BINDER <ul style="list-style-type: none">Durability of penetration at 25°CDurability of softening pointDurability of cohesion by pendulum	NPD NPD NR	EN 13074-1 followed by EN 13074-2 EN 1426 EN 1427 EN 13588
STAGE 2 DURABILITY - AGED BINDER <ul style="list-style-type: none">Durability of penetration at 25°C, 0.1 mmDurability of softening pointDurability of cohesion by pendulum	≤ 150 (Class 4) ≥ 39 (Class 7) NR	EN 13074-1 followed by EN 13074-2 and EN 14769 EN 1426 EN 1427 EN 13588
Dangerous regulated substances	NPD	EN 13808 – 5.5

Signed on behalf of Colas Ltd

Faical Lahmamsi, CEO

Place and date of issue

Birmingham, England

7/11/2024