

COLAS PRODUCTS DATA SHEET

OXIDISED BITUMEN



Oxidised Bitumen is a hot applied bitumen complying with BS EN 13304.

WHERE TO USE?

Oxidised Bitumen is approved for use as components for the manufacture of roofing, flooring, water-proofing, adhesive, sealing and anti-corrosion products.

PREPARATION

Ensure area to be treated is clean and free from dust, fuel and oil spillage.

APPLICATION

For best results use a heating kettle with an indirect heating system such as hot oil. Ensure that the heating temperature doesn't exceed 200°C and that the oil does not exceed 230°C. When hot, pour either from a melter pourer or galvanised bucket with a 'V' lip.

COVERAGE

Varies depending on the application.

PACKAGING

Oxidised Bitumen is available in 25kg silicone coated paper cylinders.

STORAGE

Oxidised Bitumen should be kept under cover and away from direct sunlight.

STANDARDS

Oxidised Bitumen comply with BS EN13304 (Bitumen and Bituminous Binders Framework for Specification of **Oxidised Bitumen's**).

SAFETY

SAFETY HANDLING PRECAUTIONS (when hot)

- Wear suitable protective clothing (heat resistant gauntlet gloves, overalls, protective footwear, face visor)
- DO NOT allow water to contact hot material
- DO NOT exceed maximum safe heating temperature
- If molten material contacts skin:
 - DO NOT attempt to remove
 - Immerse affected area in cold running water for at least 10 minutes
 - Seek medical advice without delay

NB: This product is hazardous for transportation when carried at temperatures above 100°C.

For full safety information please request the **Oxidised Bitumen** Safety Data Sheet 12A using the contact information below.

Further guidance can be found on the Eurobitume Safe Handling of Bitumen Card available on the Eurobitume Website.

NATIONAL SALES OFFICE

Loushers Lane
Warrington
Cheshire
WA4 6RZ
T: 01925 632 616
E: product.sales@colas.co.uk



WE OPEN THE WAY