


UKCA marking information – Colas Ltd

 0836	
Colas Ltd, 6210 Bishops Court, Birmingham Business Park Solihull, Birmingham, B37 7YB 13 C13 UK 0836-CPR-13/F035	
<i>BS EN 13808</i> <i>Cationic bituminous emulsion</i> <i>Leotak C40B</i> <i>intended to be used for surface treatment as tack coat</i>	
EMULSION	
<ul style="list-style-type: none"> • Efflux 2 mm at 40°C • Water effect on binder adhesion – EN 13614 • Breaking behaviour – EN 13075-1 	15-70 s Class 3 NR (Class 0) NPD
RECOVERED BINDER	
<ul style="list-style-type: none"> • Penetration at 25°C • Softening point – EN 1427 • Cohesion by pendulum – EN 13588 	≤ 220 (Class 5) ≥ 39 (Class 7) NR
STAGE 1 DURABILITY - STABILISED BINDER	
<ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	NPD NPD NR
STAGE 2 DURABILITY - AGED BINDER	
<ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	≤ 220 (Class 5) ≥ 39 (Class 7) NR
Dangerous regulated substances	NPD

**UK
CA**

0836

**Colas Ltd, 6210 Bishops Court,
Birmingham Business Park
Solihull, Birmingham, B37 7YB**

13

C13 UK 0836-CPR-13/F035

BS EN 13808
Cationic bituminous emulsion

Leotak C40B
intended to be used for surface treatment as tack coat