

COLAS PRODUCTS DATA SHEET

PREFORMED SURFACE DRESSING



Preformed Surface Dressing is an exceptionally versatile, ready-to use, hard wearing skid resistant surface for pedestrian trafficked areas. **Preformed Surfacing Dressing** comprises a high performance polymer modified bituminous binder and a layer of skid resistant calcined bauxite chippings strengthened by an integral mesh. **Preformed Surface Dressing** can be used on most surfaces, including wood, concrete, asphalt and steel.

WHERE TO USE?

- Footways
- Foot-ramps
- Footbridges
- Platforms
- Pedestrian subways

PREPARATION

Surfaces must be dry, clean and free from dust, oil and fuel spillage. **CP Primer** should be used to enhance initial adhesion of **Preformed Surface Dressing** on all sites.

APPLICATION

Roll out enough material to cover the area to be surfaced and with the backing film upwards cut the **Preformed Surface Dressing** with a sharp knife. Then prime the substrate using **CP Primer** applying as thinly and evenly as possible as too much could result in the primer bleeding through or the debonding of the **Preformed Surface Dressing**.

When the **CP Primer** is touch dry, peel off the backing film and apply the **Preformed Surface Dressing** to the surface. Take care to ensure that the positioning of the **Preformed Surface Dressing** is accurate as once laid it is extremely difficult to remove. Edges should be butt jointed or overlapped to achieve a neat close-fitting finish.

COVERAGE

Each roll will cover 5m².

PACKAGING

Preformed Surface Dressing is supplied in rolls 5m long by 1m wide, 30 rolls per pallet.

STORAGE

Rolls should be stored upright. Keep in dry store under cover and protect from frost and extreme heat.

STANDARDS

Preformed Surface Dressing is produced to a manufacturing system accredited to ISO9001.

SAFETY

For full safety information, please request the **Preformed Surface Dressing** Safety Data Sheet 14 using the contact information below.

NATIONAL SALES OFFICE

Loushers Lane
Warrington
Cheshire
WA4 6RZ
T: 01925 632 616
E: product.sales@colas.co.uk



WE OPEN THE WAY